

// 748AA



**Rig supply soft wall - Bulk material 20 bar (300 psi)**

**Tube:** black conductive NR - abrasion resistant.

**Reinforcement:** high tensile textile cords - antistatic wire.

**Cover:** black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.

**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Specially designed for reeling applications and weak link couplings use.

Tensile end load resistance:

ID 4" 6.000 kg

ID 5" 10.000 kg

**ABS Type approved hose assemblies.**

Electrically continuous.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| ↔     |    | ↔      |      | ⬇   | ⬆   | ↷   |      | ↶     |       | ⤴ | ⚖     |       |
|-------|----|--------|------|-----|-----|-----|------|-------|-------|---|-------|-------|
| mm    | in | mm     | in   | bar | psi | bar | psi  | mm    | in    | % | kg/m  | lb/ft |
| 102,0 | 4" | 122,00 | 4,80 | 20  | 300 | 80  | 1200 | 612,0 | 24,09 |   | 4,460 | 3,00  |
| 127,0 | 5" | 149,00 | 5,87 | 20  | 300 | 80  | 1200 | 762,0 | 30,00 |   | 6,320 | 4,25  |

// 715AA



**Rig supply hard wall - Bulk material 20 bar (300 psi)**

**Tube:** black conductive NR - abrasion resistant.

**Reinforcement:** high tensile textile cords with embedded steel helix wire - antistatic wire.

**Cover:** black conductive CR- abrasion, ozone, hydrocarbon and fire resistant.

**Application:** bulk material, barite and dry cement transfer from supply vessels to offshore platforms.

Also available in self floating version. Reserve buoyancy calculated according to GMPHOM 2009 standard.

Tensile end load resistance:

ID 4" 7.000 kg

ID 5" 10.000 kg

**ABS Type approved hose assemblies.**

Electrically continuous.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| ↔     |    | ↔      |      | ⬇   | ⬆   | ↷   |      | ↶     |       | ⤴  | ⚖     |       |
|-------|----|--------|------|-----|-----|-----|------|-------|-------|----|-------|-------|
| mm    | in | mm     | in   | bar | psi | bar | psi  | mm    | in    | %  | kg/m  | lb/ft |
| 102,0 | 4" | 124,00 | 4,88 | 20  | 300 | 80  | 1200 | 510,0 | 20,08 | 90 | 6,060 | 4,08  |
| 102,0 | 4" | 124,00 | 4,88 | 20  | 300 | 80  | 1200 | 510,0 | 20,08 | 90 | 6,060 | 4,08  |
| 127,0 | 5" | 151,00 | 5,94 | 20  | 300 | 80  | 1200 | 635,0 | 25,00 | 90 | 8,530 | 5,74  |